



Series 402 Hornet™ Hot Cathode Miniature-Ionization Vacuum Gauge with Dual Convection

Hot Cathode Bayard-Alpert Ionization gauge with space-saving built-in controller and display operates 3 different gauges

Full range measurements from 1×10^{-9} to 1,000 Torr plus monitoring of your foreline

Low cost of ownership: Significant cost reduction in controller, space, cabling costs and sensor replacement

Built-in bright digital OLED display with wide viewing angle, RS485 digital interface, 3 setpoint relays and 3 log-linear analog outputs

Dual hot filament design, rugged and compact metal construction

The first modular ionization vacuum gauge capable of operating two convection gauges



IGM402 Ionization Gauge with Dual Convection

InstruTech IGM402 Hornet™ Modules

Technology

Gauge The IGM402 *Hornet* ionization vacuum gauge module provides the basic signal conditioning required to turn the gauge into a complete measuring instrument. It incorporates numerous design features to enhance performance and reduce cost. The electrometer circuit auto zeroes to ensure that the readings are not subject to temperature drift, eliminating the need for unnecessary, expensive circuitry which further reduces the cost.

Multiple Gauges The IGM402 *Hornet* is capable of operating two external convection vacuum gauges simultaneously.

Full Range Measurement The IGM402 *Hornet* can combine the vacuum measurement from the ion gauge and a convection gauge to provide full range measurements from 1×10^{-9} Torr to 1,000 Torr, or simply operate the ion gauge and the two convection gauges as individual gauges.

Display The standard built-in bright OLED display provides a convenient user interface for setup and operation of the vacuum gauges. The display screen can show all three measurements on the same screen or display them sequentially. Service screens allow monitoring of filament operation. Error messages are displayed for several common fault conditions.

Operation The operation of the gauge including degas, filament on/off and emission current is set by the front panel push buttons, digital inputs or RS485 commands.

Sensor For general vacuum applications, dual yttria coated filaments are offered for use with air and inert gases such as N_2 , argon, etc. Dual tungsten filaments are available for use with gases that may not be compatible with yttria coated filaments.

Low Cost of Ownership

Controller The compact modular design with the built-in controller and display operates three different gauges without requiring expensive external controllers.

Space No rack space required. The modular design negates the need for expensive and limited rack space.

Cabling Cost The cabling cost to connect a nude/glass ionization gauge to a rack-mount controller can be excessive and installation is time consuming. With the IGM402 no ion gauge cable is required and one 10 ft. convection gauge cable is included.

Sensor Replacement Many full range combination gauges provide measurements from atmosphere to high vacuum with multiple sensors built into one assembly. A sensor failure may require replacement of the entire sensor assembly often approaching 50% of the initial cost of the vacuum gauge itself.

The IGM402 *Hornet* provides an alternative to these other gauges by combining the vacuum measurements from the ion gauge and one of the convection gauges to provide a full range gauge. A sensor replacement requires only the replacement of the damaged sensor and not all the other sensors at once.


The IGM402 *Hornet* sensor assembly can be easily replaced in the field.

Additional Point of Use In addition to the ion gauge and one convection gauge, the IGM402 *Hornet* can provide vacuum measurements from a second convection gauge without the need for another expensive controller. This results in significant cost savings for monitoring the foreline or an additional point of use.

Specifications

measurement range:	ionization (IG)	1 x 10 ⁻⁹ to 5 x 10 ⁻² Torr / 1.3 x 10 ⁻⁹ to 6.7 x 10 ⁻² mbar / 1.3 x 10 ⁻⁷ to 6.7 Pa
	convection (CG)	1 x 10 ⁻⁴ to 1,000 Torr / 1.3 x 10 ⁻⁴ to 1,333 mbar / 1.3 x 10 ⁻² Pa to 133 kPa
	used as a full range gauge (IG+CG)	1 x 10 ⁻⁹ to 1,000 Torr / 1.3 x 10 ⁻⁹ to 1,333 mbar / 1.3 x 10 ⁻⁷ Pa to 133 kPa
accuracy - N ₂ (typical)		1 x 10 ⁻⁸ to 1 x 10 ⁻³ Torr; ± 15% of reading 1 x 10 ⁻³ to 400 Torr; ± 10% of reading, 400 to 1,000 Torr; ±2.5% of reading
repeatability - (typical)		1 x 10 ⁻⁸ to 1 x 10 ⁻³ Torr; ± 5% of reading, 1 x 10 ⁻³ to 1,000 Torr; ±2% of reading
display		bright OLED display, 3 digits plus 1 digit exponent, user-selectable Torr, mbar, or Pa
functionality		ionization gauge can operate up to 2 convection gauges
materials exposed to gases		dual filaments: yttria coated iridium or optional tungsten Ion collector: tungsten Grid: 304 Stainless Steel Others: 316/304 SS, glass, nickel
sensitivity		factory pre-set. Also user adjustable between 2 to 99
x-ray limit		< 5 x 10 ⁻¹⁰ Torr, < 6.7 x 10 ⁻¹⁰ mbar, < 6.7 x 10 ⁻⁸ Pa
emission current		100 µA, 4 mA
degas		3 W, electron bombardment
internal gauge volume		1.0 in ³ (16.4 cm ³)
overpressure protection		IG filament turns off at factory default of 5 x 10 ⁻² Torr; also user adjustable below 50 mTorr
temperature		operating; 0 to + 40 °C storage; -40 to + 70 °C
bakeout temperature		200 °C (sensor only - electronics removed)
humidity		0 to 95% relative humidity, non-condensing
weight		0.6 lb. (0.27 kg) with NW25 KF flange
housing (electronics)		aluminum extrusion
mounting orientation		any
serial communications		RS485 - User selectable ASCII protocol, or BINARY protocol using InstruTech CRC8, minimum command interval: 50 ms for both protocols
analog outputs (3 total)	IG	one log-linear 0 to 9 Vdc, 1 V/decade, or
	IG+CG	one log-linear 0.5 to 7 Vdc, 0.5 V/decade, and
	CG	two log-linear 1 to 8 Vdc, 1 V/decade or non-linear 0.375 to 5.659 Vdc
setpoint relays (3 total)		three single-pole, double-throw (SPDT), 1A at 30 Vdc resistive, or ac non-inductive
status outputs		degas & filament on/off status via display messages, open collector transistor or RS485
input signal		degas and filament on/off & emission current are set by continuity to ground using digital inputs, RS485 or manually using front panel push button
filament selection		filament 1 or 2 selectable via front panel push buttons or RS485 commands
input power		20 to 28 Vdc, 30 W protected against power reversal and transient over-voltages
connectors		(2) 9-pin D-Sub, (2) terminal blocks, (2) convection gauge connectors
convection gauge compatibility		InstruTech CVG101 <i>Worker Bee</i> [™] or Granville-Phillips [®] 275 Convector [®]
CE compliance		EMC Directive 2014/30/EU, EN55011, EN61000-6-2, EN61000-6-4, EN61326-1, EN61010-1
environmental		RoHS

Fitting	dimension A
NW16KF	1.45 in. (37mm)
NW25KF	1.45 in. (37mm)
NW40KF	1.45 in. (37mm)
1 1/3 in. Mini-CF	1.85 in. (47 mm)
2 3/4 in. Conflat [®]	1.70 in. (43 mm)
3/4 in. Tube	2.16 in. (55 mm)
1/2 in. VCR	2.58 in. (65 mm)



Ordering Information

Part Numbers

IGM402 Fittings / Flanges	With Yttria Filaments	With Tungsten Filaments	Convection Gauge Cable Assembly	Replacement / Spare IG Sensor	
				Yttria	Tungsten
NW16KF	IGM402YBD	IGM402TBD	HB431-1-3F (3 ft.)	IG4YB	IG4TB
NW25KF	IGM402YCD	IGM402TCD	HB431-1-10F (10 ft.)	IG4YC	IG4TC
NW40KF	IGM402YDD	IGM402TDD	HB431-1-25F (25 ft.)	IG4YD	IG4TD
1 1/3 in. Mini-CF / NW 16CF Mini- Conflat [®]	IGM402YED	IGM402TED	HB431-1-50F (50 ft.)	IG4YE	IG4TE
2 3/4 in. CF / NW35CF Conflat [®]	IGM402YFD	IGM402TFD	>50 ft. Consult Factory	IG4YF	IG4TF
3/4 in. Tube (3/4 in. O.D. O-ring compression)	IGM402YAD	IGM402TAD		IG4YA	IG4TA
1/2 in. Cajon [®] 8VCR [®] female	IGM402YHD	IGM402THD		IG4YH	IG4TH

Note: CVG101 Convection Gauges must be ordered separately. Please see part numbers in CVG101 data sheet.

Granville-Phillips[®] and Convector[®] are registered trademarks of MKS Instruments, Andover, MA.
Conflat[®] is a registered trademark of Varian, Inc. / Agilent Technologies, Lexington, MA.

Swagelok[®], Cajon[®], VCR[®] are registered trademarks of the Swagelok Company, Solon, OH.



InstruTech[®]
1475 S. Fordham Street
Longmont, CO 80503 USA

Phone +1-303-651-0551
Fax +1-303-678-1754
E-mail info@instrutechinc.com
Web www.instrutechinc.com